



**Fs- Flange Size**

1", 1-1/2", and 2", refer to table 1.6 on page 13  
Other

**Pr- Flange Rating**

150#, 300#, 400#, 600#, 900#, 1500# and 2500#

**Ft- Flange Thickness**

0.375" (9.5)  
Other

**H - Head Length**

2.250" (57.2)  
3.250" (82.6)  
Other

**Pd- Pipe Diameter**

1.315" (33.4), for 1" flange size  
1.900" (48.3), for 1-1/2" flange size  
2.375" (60.3), for 2" flange size  
Other

**U - Insertion Length**

decimal units

**Tt - Tip Thickness**

0.250" (6.4)  
Other

**A - Stem Length**

decimal units

**M - Material**

refer to table 2.0 on page 23

**B - Bore Size**

0.260 (6.6)  
0.385 (9.8)  
0.512" (13.0)  
Other

**V - Tip Diameter**

0.625, (15.9), refer to table 1.8 on page 13  
0.750", (19.1), refer to table 1.8 on page 13  
Other, refer to table 1.8 on page 13

**O - Options**

refer to page 22

**Sample Part No.:** P15 - 150# - 0.375" - 3.250" - 2.375" - 6.000" - 0.250" - 9.000" - R/RL - 0.260" - 0.750" - DR11a, SC3

**Notes**

1. Most Vanstone thermowells are fabricated from one piece bar stock. A two piece construction could be considered for economic reasons.
2. Contact a sales representative when requiring a thermowell not listed in this catalogue.
3. Metric dimensions are in brackets.